

JCW-CST10

Fully Automatic 3 Sided Crimping Machine Crimps 2 Wires into 1 Terminal



Features

- High flexibility, compatible with Wire pre-feeder, CFM, wire stacker
- 7" touch screen, English / Chinese [other languages on request]
- Process 2 different sized wires and 3 different crimp terminals

Technical Data

Function	2 Wires, 3 Terminals, 3 Crimping Units, Cut depth, Crimp position, Pull-off length, Wire detector, Knot detector, Air pressure detector		
Wire cross-section	0.05 - 2 mm ² (AWG 32 - 14)	/	Cut length (L) 41 - 99999 mm [Short size on request]
Cut accuracy	L < 100mm: 0.2 mm ± 0.002 x L L > 100mm: 0.5 mm ± 0.002 x L		
Cut length increment	0.01 mm, max 5.5 mm	/	Production rate 2000 sets/h
Strip length	Front end: 0.5 - 8 mm. Rear-end: 0.1 - 10 mm	/	Crimping force 20 KN (2.0 tons) [40 KN on request]
Power supply	AC 110V - 220V ± 10%, 50 / 60 Hz	/	Air supply 0.4 - 0.7 MPa [Clean and dry air]
Dimensions	L 1000 x W 1600 x H 1800 mm	/	Weight 550 KG
Detection	Wire lack, Terminal crimping, Wire knot, Air pressure		